

## RUBBER WHEELS



 AIRTRADE  
a member of  
for Third World  
Producers

## RUBBER WHEELS WITH ALUMINUM CENTRE

Tread: Rubber

Centre: Aluminum

Color: As per request

Hardness: As per request

Diameter range: 100–300mm

Load capacity: 100–700kgs

Firmly bonded, 75 ± 3 shore A






Abrasion-resistant, elastic, low rolling resistance

Bearing: Ball Bearing

Temperature range: -20°C +50°C

Working speed: 4km/h



SERIES RAAF					
RAAF-100/40-15B	100	40	45	15	100
RAAF-125/40-15B	125	40	45	15	150
RAAF-125/50-20B-1	125	50	50	20	200
RAAF-125/50-20B-2	125	50	60	20	200
RAAF-150/50-20B-1	150	50	50	20	300
RAAF-150/50-20B-2	150	50	60	20	300
RAAF-160/50-20B-1	160	50	50	20	350
RAAF-160/50-20B-2	160	50	60	20	350
RAAF-170/50-20B	170	50	58	20	350
RAAF-180/50-20B-1	180	50	50	20	400
RAAF-180/50-20B-2	180	50	60	20	400
RAAF-200/50-20B-1	200	50	50	20	450
RAAF-200/50-20B-2	200	50	60	20	450
RAAF-250/50-20B-1	250	50	50	20	550
RAAF-250/50-20B-2	250	50	60	20	550
RAAF-300/57-25B	300	57	60	25	650
RAAF-300/57-25B	300	57	60	30	650
RAAF-300/60-25B	300	60	60	25	700



## RUBBER WHEELS WITH ALUMINUM CENTRE

Tread: Rubber

Centre: Aluminum

Color: As per request

Hardness:  $75 \pm 3$  shore A

Diameter range: 100–300mm






Load capacity: 100–700kgs

Firmly bonded

Abrasion-resistant, elastic, low rolling resistance

Temperature range:  $-20^{\circ}\text{C}$   $+50^{\circ}\text{C}$

Working speed: 4km/h





SERIES RABW					
RABW-100/38-12B-1	100	38	41	12	100
RABW-100/38-12B-2	100	38	44	12	100
RABW-100/40-12B	100	40	40	12	100
RABW-125/38-15B	125	38	41	15	150
RABW-150/38-15B	150	38	41	15	250
RABW-200/63-20B	200	63	70	20	480
RABW-200/76-25B	200	76	82	25	500
RABW-250/63-20B	250	63	70	20	580
RABW-250/76-25B	250	76	82	25	600
RABW-300/76-25B	300	76	82	25	700

## RUBBER WHEELS WITH ALUMINUM CENTRE

Tread: Rubber  
 Centre: Aluminum  
 Color: As per request  
 Hardness: 75 ± 3 shore A  
 Diameter range: 4-12inch  
 Load capacity: 250-1400lbs

Firmly bonded  
 Abrasion-resistant, elastic, low rolling resistance  
 Bearing: Ball Bearing  
 Temperature range: -20°C +50°C  
 Working speed: 4km/h



SERIES RACT					
RADI-04/20R	4	2	2-3/16	1-3/16	250
RADI-05/15R	5	1-1/2	1-5/8	1-3/16	300
RADI-05/20R	5	2	2-3/16	1-3/16	500
RADI-06/15R	6	1-1/2	1-5/8	1-3/16	500
RADI-06/20R	6	2	2-3/16	1-3/16	550
RADI-08/15R	8	1-5/8	1-13/16	1-3/8	700
RADI-08/20R	8	2	2-3/16	1-3/16	800
RADI-08/25R	8	2-1/2	2-3/4	1-9/16	900
RADI-08/30R	8	3	3-1/4	1-15/16	1000
RADI-10/25R	10	2-1/2	2-3/4	1-9/16	1000
RADI-10/30R	10	3	3-1/4	1-15/16	1200
RADI-12/30R	12	3	3-1/4	1-15/16	1400



## RUBBER WHEELS WITH ALUMINUM CENTRE

### Crown Rubber

Tread: Black & Grey Rubber

Centre: Aluminum

Color: As per request

Hardness:  $75 \pm 3$  shore A

Diameter range: 6-8in

Load capacity: 750-1000kgs

Firmly bonded

Abrasion-resistant, elastic, low rolling resistance

Bearing: Plain bearing

Temperature range:  $-20^{\circ}\text{C}$   $+50^{\circ}\text{C}$

Working speed: 4km/h

SERIES RACB	D	T	w	d	LBS
RACB-06/20R	6	2	2-3/16	1-3/16	750
RACB-08/20R	8	2	2-3/16	1-3/16	1000
RACB-06/20B	6	2	2-3/16	17	800
RACG-06/20R	6	2	2-3/16	1-3/16	750
RACG-08/20R	8	2	2-3/16	1-3/16	1000
RACG-06/20B	6	2	2-3/16	17	800

## RUBBER WHEELS WITH CAST IRON CENTRE

Tread: Rubber  
 Centre: Cast Iron  
 Color: As per request  
 Hardness:  $75 \pm 3$  shore A  
 Diameter range: 100–300mm  
 Load capacity: 150–800kgs  
 Firmly bonded  
 Abrasion-resistant, elastic, low rolling resistance  
 Bearing: Ball Bearing  
 Temperature range:  $-20^{\circ}\text{C}$   $+50^{\circ}\text{C}$   
 Working speed: 4km/h



SERIES RCAL/RCBV						
RCBV-100/50-20B	100	50	60	60	20	150
RCBV-125/40-10B	125	40	46	46	10	200
RCBV-125/50-20B	125	50	60	59	20	250
RCBV-200/50-20B	200	50	60	62	20	600
RCBV-250/50-25B	250	50	60	70	25	700
RCBV-250/57-25B	250	57	60	70	25	750
RCBV-300/50-25B	300	50	60	67	25	750
RCBV-300/90-30B	300	90	100	88	30	800

## RUBBER WHEELS WITH CAST IRON CENTRE

Tread: Rubber  
 Centre: Cast Iron  
 Color: As per request  
 Hardness:  $75 \pm 3$  shore A  
 Diameter range: 100–300mm  
 Load capacity: 150–800kgs  
 Firmly bonded  
 Abrasion-resistant, elastic, low rolling resistance  
 Bearing: Plain Bearing  
 Temperature range:  $-20^{\circ}\text{C}$   $+50^{\circ}\text{C}$   
 Working speed: 4km/h









SERIES RCAL						
RCAL-100/34-20R	100	34	45	35	20	150
RCAL-125/50-31L	125	50	60	44	31.5	250
RCAL-150/50-31L	150	50	60	44	31.5	400
RCAL-200/50-31L	200	50	60	52	31.5	600
RCAL-250/50-36L	250	50	60	70	36.5	700
RCAL-300/50-36L	300	50	60	70	36.5	800

## RUBBER WHEELS WITH CAST IRON CENTRE



Tread: Rubber  
 Centre: Cast Iron  
 Color: As per request  
 Hardness:  $75 \pm 3$  shore A  
 Diameter range: 4–12in  
 Load capacity: 300–1400lbs

Firmly bonded  
 Abrasion-resistant, elastic, low rolling resistance  
 Bearing: Plain Bearing  
 Temperature range:  $-20^{\circ}\text{C}$   $+50^{\circ}\text{C}$   
 Working speed: 4km/h

SERIES RCCI						
RCCI-04/20R	4	2	2-3/16	1-11/16	1-3/16	300
RCCI-05/20R	5	2	2-3/16	1-11/16	1-3/16	450
RCCI-06/20R	6	2	2-3/16	1-11/16	1-3/16	500
RCCI-06/25AR	6	2-1/2	2-3/4	1-11/16	1-3/16	550
RCCI-06/25CR	6	2-1/2	3-1/4	2-1/2	1-15/16	700
RCCI-06/30R	6	3	3-1/4	2-1/2	1-15/16	750
RCCI-08/20R	8	2	2-3/16	1-11/16	1-3/16	800
RCCI-08/25AR	8	2-1/2	2-3/4	1-11/16	1-3/16	800
RCCI-08/25CR	8	2-1/2	3-1/4	2-1/2	1-15/16	900
RCCI-08/30R	8	3	3-1/4	2-1/2	1-15/16	1200
RCCI-10/25AR	10	2-1/2	2-3/4	1-11/16	1-3/16	900
RCCI-10/25CR	10	2-1/2	3-1/4	2-1/2	1-15/16	1000
RCCI-10/30R	10	3	3-1/4	2-1/2	1-15/16	1300
RCCI-12/25CR	12	2-1/2	3-1/4	2-1/2	1-15/16	1100
RCCI-12/30R	12	3	3-1/4	2-1/2	1-15/16	1400