

DRIVE WHEELS



DRIVE WHEELS



Tread: VULKOLLAN®
 Centre: Cast iron
 Color: Light Brown
 Hardness: 92 ± 3 shore A
 Diameter range: 230–254mm
 Load capacity: 1300–2100kgs

Firmly bonded
 Abrasion-resistant, elastic, low rolling resistance
 Temperature range: -30°C +120°C
 Working speed: 20km/h
 The tyre is firmly bonded to the cast iron with chemical adhesives

SERIES DWPS						
DWPS-230/70	230	70	45	14	70	1300
DWPS-250/80	250	80	80	15	112	1600
DWPS-230/70	230	70	45	14	70	1300
DWPS-230/75-45	230	75	45	13	70	1500
DWPS-230/75-80	230	75	80	14	112	1400
DWPS-230/80	230	80	65	14	95	1150
DWPS-230/82	230	82	45	14	70	1500
DWPS-230/90	230	90	45	13	70	1300
DWPS-250/75-80A	250	75	80	15.5	112	1450
DWPS-250/75-80B	250	75	80	18.5	112	1450
DWPS-250/80	250	80	80	15	112	1600
DWPS-250/82	250	82	80	18.5	112	1700
DWPS-254/102	254	102	80	18	112	2000
DWPS-200/85	200	85	50	10.5	72	1300
DWPS-230/80	230	80	65	14	95	1150
DWPS-230/90-30	230	90	30	13.5	65	1650
DWPS-230/90-65	230	90	65	13	95	1650
DWPS-254/100	254	100	80	18.5	112	2100

DRIVE WHEELS

Tread: Elastic rubber-tyre
 Centre: Cast iron, Painted
 Color: Black
 Hardness: 75 ± 3 shore A
 Diameter range: 200–254mm

Firmly bonded
 Abrasion-resistant, elastic, low rolling resistance
 Temperature range: -30°C +80°C
 Working speed: 16km/h
 Load capacity: 350–850kgs
 The tyre is firmly bonded to the cast iron with chemical adhesives





SERIES DWRB	D	T	M	H	Ø	Kg
DWRB-200/75	200	75	M10	10.5	52	350
DWRB-200/85	200	85	50	10.5	72	440
DWRB-230/70	230	70	45	14	70	315
DWRB-230/75	230	75	45	13	70	600
DWRB-230/82	230	82	45	14	70	530
DWRB-230/85	230	85	80	14	112	700
DWRB-230/90-65	230	90	65	13	95	750
DWRB-230/90-30	230	90	30	13	65	500
DWRB-230/90-45	230	90	45	13	70	750
DWRB-233/85	233	85	50	12.5	80	700
DWRB-250/105	250	105	80	18.5	112	850
DWRB-254/102	254	102	80	18	112	800

DRIVE WHEELS



Tread: Haiyou PUGT-tyre
 Centre: Cast iron and steel
 Color: As per request
 Hardness: 92 ± 3 shore A
 Diameter range: 125–350mm
 Load capacity: 520–3100kgs

Firmly bonded
 Abrasion-resistant, elastic, low rolling resistance
 Temperature range: -30°C +80°C
 Working speed: 20km/h
 The tyre is firmly bonded to the cast iron with chemical adhesives

SERIES DWPS				
HSTY-125/50	125	50	75	520
HSTY-150/40	150	40	100	600
HSTY-150/50	150	50	100	650
HSTY-150/75	150	75	100	950
HSTY-180/50	180	50	120	750
HSTY-200/75	200	75	100	1040
HSTY-200/80	200	80	120	1250
HSTY-200/105	200	105	120	1600
HSTY-230/100	230	100	140	1750
HSTY-250/80	250	80	170	1600
HSTY-250/105	250	105	170	2000
HSTY-285/75	285	75	220	1800
HSTY-285/100	285	100	228	2400
HSTY-285/125	285	125	220	2400
HSTY-300/90	300	90	203	2000
HSTY-343/114	343	114	225	2700
HSTY-350/110	350	110	270	3100